

Undersink Boil/Hot Water Dispenser Combo Heat Series



PBCH 40/12
 Undersink Boil/Hot
 water dispenser
 2 in 1 Module



PB 5380 sinktop
 dispenser tap

FEATURES:

- Low level dispensing height improves user safety
- Supplies 97°C water to a rugged and robust sinktop tap for hot beverages. Also supplies tempered hot water at 55°C (easily adjusted to 45°C) to any hot tap or mixer at the sink for washing dishes and other sanitary purposes
- No need to specify the usual separate oversink water boiler and undersink hot water cylinders for your staffroom - the Combo Heat performs both functions. It utilises a single cylinder incorporating a specially designed internal heat exchanger (in addition can supply a nearby ablution washbasin tap)

PRODUCT DESCRIPTION:

- Undersink design maximises space over the bench top, also ideal for island kitchen designs
- Saves power - one cylinder radiates much less wasted heat than two separate units
- A large expansion chamber removes vapour locks from the system - vented via the boiler tap, therefore no dripping, steaming or spattering. Boiling water is always dispensed smoothly and safely
- The dispenser tap is mounted on the sinktop on a corner of the sink
- Includes a PB 5380 Torrens complete Sinktop Tap Assembly (pictured above)

OPTIONS AVAILABLE:

- 10" Water Filter (10 micron EP 10 Carbon Block cartridge or 0.5 micron SCBS-10 Silver impregnated Carbon Block cartridge, please specify)
- D809 Heavy Duty Power Timer available, which saves electricity by automatically turning off the water dispenser overnight when not needed (3 pin plug only)

SPECIFY AS: Powerboil (followed by product code)

PRODUCT CODE	RATING KW	NO OF CUPS	CUPS/HOUR RECOVERY	LITRES OF HOT WATER 55°C	STAFF NUMBERS	POWER SUPPLY REQUIRMENTS	DIMENSIONS MM
PBCH 40/12	2.4	40	120	12	40	One 3 pin plug	480H 245W 290D
PBCH 80/12	4.8	80	240	12	80	Hardwired	480H 245W 290D

Please note: Recommended staff numbers are based upon pouring 200ml cups without interruption