

Undersink Automatic Water Boiler - PBTD Series



PBDT 5.0
Undersink Boiler



PB 5380 Sinktop
Dispenser Tap

FEATURES:

- Mounted under the sink out of sight
- The boiler unit is vented through the tap - no cupboard vents required
- Plumbers can easily install and service these units, no costly technicians required
- Low maintenance costs (only one moving part in the operating system)

PRODUCT DESCRIPTION:

- Single hot water storage tank, is housed within an insulated rectangular cabinet positioned under the sink
- Large expansion chamber and venturi ensures no steaming or dripping from the tap
- Storage temperature is maintained at 97°C by a powerful and accurate 10 amp computerised element
- Includes a PB 5380 Torrens complete Sinktop Tap Assembly (pictured above)

OPTIONS AVAILABLE:

- 10" Water Filter (10 micron EP 10 Carbon Block cartridge or 0.5 micron SCBS-10 Silver impregnated Carbon Block cartridge, please specify)
- D809 Heavy Duty Power Timer available, which saves electricity by automatically turning off the boiler overnight when not needed (3 pin plug only)

SPECIFY AS: Powerboil (followed by product code)

PRODUCT CODE	RATING KW	NO OF CUPS	CUPS/HOUR RECOVERY	STAFF NUMBERS	POWER SUPPLY REQUIRMENTS	DIMENSIONS MM
PBTD 2.0	1.8	10	90	10	One power socket	335H 180W 150D
PBTD 2.5	2.4	15	120	15	One power socket	325H 245W 290D
PBTD 5.0	2.4	40	120	40	One power socket	480H 245W 290D
PBTD 5.0 4.8kw	4.8	80	240	80	Hardwired	480H 245W 290D

Please note: Recommended staff numbers are based upon pouring 200ml cups without interruption