

Undersink Boil, Chill & Hot Water Dispenser TripleMate Series



Undersink Boil/Hot
and Chiller Modules

Stylish sinktop mounted boiling
and chilled water dispenser tap

FEATURES:

- Supplies filtered boiling and chilled water to a Sinktop Duo dispenser tap
- In addition, can supply hot water via a built in heat exchanger to any sinktop mixer of choice for dishwashing and sanitary purposes – no need for kitchenette underbench HWCs
- Boiling and chilled water are both fully filtered. Included is a EP 10 Carbon Block cartridge (SCBC-10 is available as an option)
- Unique boiler expansion chamber ensures safe and splatter-free dispensing of boiling water
- Very reliable push-through design. No expensive electronics, valves or solenoids to service
- Chiller options of economical 1/8 Hp and Powerful 1/4 Hp power ratings

PRODUCT DESCRIPTION:

- Stylish Sinktop Duo dispenser tap with light operated 1/4 turn levers. Boiler is fully vented through tap
- Separate boiler and chiller modules and external water filter ensures easy servicing by plumbers and low long-term maintenance costs
- Boiler options of powerful 2.4 Kw plug-in and 4.8 Kw hardwired boiler heating elements ensure no shortage of boiling water in any size staffroom
- Included is a PB WP30 PowerBoil Duo Boil/Chill Sinktop Tap (pictured above)
- Optional D809 Heavy Duty Power Timer available, which saves electricity by automatically turning off the dispensers overnight when not needed (3 pin plug only)

SPECIFY AS: Powerboil (followed by product code)

PRODUCT CODE	RATING KW	NO OF CUPS (BOILING) AT ONCE	CUPS/HOUR RECOVERY BOILING	LITRES HOT WATER AT ONCE	CUPS/HOUR CHILLED (POWER RATING)
PBTM 40/12/40	2.4	40	120	12	40 (1/8 HP)
PBTM 40/12/100	2.4	40	120	12	100 (1/4 HP)
PBTM 80/24/40	4.8	80	240	24	40 (1/8 HP)
PBTM 80/24/100	4.8	80	240	24	100 (1/4 HP)

DIMENSIONS FOR BOIL/HOT MODULES (mm):
480H 325W 345D

DIMENSIONS FOR WATER CHILLER MODULES (mm):
 For 40 cup module: 190H 315W 415D
 For 100 cup module: 310H 180W 500D